

Campro

CB-FD204P

Face Detection & Perimeter Protection

2MP SMART AI Day & Night Fixed-Focal Dome Camera



Model No.	CB-FD204P		
Digital Video Processor			
Sensor	1/2.8" 2MP CMOS Sensor		
RAM & Flash	256MB RAM / 128MB ROM		
Minimum Illumination	0.0001Lux@F1.2(AGC ON), 0 Lux (IR on)		
Shutter Speed	1/3 s to 1/100, 000 s		
Day / Night	Auto, Dual IR-Cut Filter, D/N Sensitive Switch / Mixed Mode Switch		
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°		
Lens			
Lens	2.8mm / 3.6mm / 6.0mm Fixed Focal Lens		
Max. Aperture Ratio	F No. 1.6		
Min. Object Distance	2M		
Lens Mount	M12		
Max. Aperture	F1.6		
Iris Type	Auto Iris		
Focal Length & FOV			
Lens	2.8mm	3.6mm	6.0mm
Angle of View (H)	107°	92°	57°
Angle of View (V)	56°	45°	30°
Angle of View (O)	127°	111°	65°
DORI			

DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	2.8mm	44.1	17.7	8.8	4.4
	3.6mm	58.9	23.6	11.8	5.9
	6.0mm	82.8	33.1	16.6	8.3
Illuminator					
Supplement Light Type	IR Led*2 up to 40M / 850nm				
Supplement Light Range	40M				
Illuminator Control	Auto / Manual				
Smart IR	Supported				
Video					
Max Resolution	1920*1080@50/60fps				
Main Stream	50/60fps (2MP: 1920*1080, 960P: 1280*960, 720P: 1280*720)				
Sub Stream	50/60fps (704*576, 640*480, 640*360)				
Third Stream	50/60fps (1280*720, 640*480, 640*360)				
Video Compression	Main stream: H.265+/H.265/H.264+/H.264 Sub-stream: H.265+/H.265/H.264+/H.264/MJPEG Third stream: H.265+/H.265/H.264+/H.264				
Video Bit Rate	H.265: 56 Kbps~8912 Kbps / H.264: 56 Kbps~8912 Kbps				
U-code	Supported				
Bit Rate Control	CBR / VBR				
Scalable Video Coding (SVC)	H.265 and H.264 Encoding (H.265+ (Ultra H.265)/H.265/H.264+/H.264/MJPEG)				
Audio					
Audio Encoding	G.711a, G.711Mu, G.726, G.726ASF				
Audio Bite Rate	Minimum 64 Kbps or Higher				
Reduce Echo	Supported				
Noise Filtering	Supported				
Built-in MIC	Supported				
Built-in Speaker	Supported				
Two-way Audio	Supported (Built in Microphone & Speaker)				
Other Audio Function	Support Auto Gain, Audio Input/Output Volume				
Network					
Network Protocol	DHCP, DNS, DDNS, FTP, HTTP, HTTPS, ICMP, IGMP, IPv4, IPv6, NTP, ONVIF, P2P, PPPOE, QoS, RTP, RTSP, SMTP, SNMP, TCP/IP, UDP, UPnP, 802.1X				
Protocol	ONVIF / CGI / P2P				
Simultaneous Live View	Up to 16 channels				
API	Open Network Video Interface Profile S, G, T, SDK				
User/Host	20 User (Total bandwidth: 80M), 2 user levels: administrator and user				
Security	Password Protection, Complicated Password, HTTPS Encryption, 802. 1X Authentication (EAP-MD5), Watermark, Basic and Digest, Authentication for HTTP/HTTPS, WSSE and Digest Authentication for Open Network Video Interface, RTP/RTSP over HTTPS, Security Audit log, TLS 1.2, TLS 1.3, Host Authentication (MAC address)				
Video Management Software	IE / Web / PC Client Software / App				

Mobile Client	iOS, Android
Web Browser	Plug-in required live view: IE 10+, Plug-in free live view: Chrome 57.0+, Firefox 52.0+, Local service: Chrome 57.0+, Firefox 52.0+
Smooth Streaming	Yes
Image	
OSD	Minimum 4 OSDs
Privacy Mask	Up to 4 Areas (programmable polygon privacy masks)
ROI	Support 8 Areas
Corridor Mode	Supported
Corridor Pattern	Standard / Gorgeous
WDR	True WDR, ≥140dB
DNR	3D DNR (Auto / Manual)
S/N Ratio	≥ 56dB
BLC / White Balance	Auto / Lock White Balance / Fluorescent Lamp / Filament Lamp / Fluorescent Lamp / HM
Image Control	Brightness, Contrast, Saturation, Sharpness
Gain Control	Auto
Flip	Normal / Vertical / Horizontal / 0° / 90° / 180° / 270°
Mirror	Supported
Highlight Compensation	Support
FLC	FLC Supported
Backlight Compensation	BLC Supported
Suppression	HLC Supported
Penetrating Fog	Supported
Vernier Focusing	Supported
All Electric Rectifier	Supported
Interface	
Audio	1CH Input / 1CH Output
Alarm	1CH Input / 1CH Output
LAN Ports	RJ45*1, 10M /100M Base-T
Storage	Support Max. 256G Micro SD / SDHC / SDXC(FAT32), FTP
Event	
Motion Detection	Multiple Detection Zones, Variable Sensitivity Levels
Snapshot	Support JPEG Format
Security Features	Pass word, Watermark
OSD	Channel Name, Date & Time, Image Overlay
Storage	Support FTP Storage
Alarm	Arming/Disarming, Sound Alarm, Light Alarm, Mask Alarm, Support Network Anomaly etc.
Linkage	FTP / Memory Card E-mail, Notify Surveillance Center, Trigger Recording, Trigger Capture
Alarm Event	Disconnection; IP Conflict; No SD Card; Capacity Warning; SD Card Error
Intelligent Analysis	
Basic Detection	Face Detection, Cross Line, Intrusion (Based on Human and Vehicle Detection), Motion

	Detection, Ultra Motion Detection, Tampering Alarm, Audio Detection, Watermark, IP address Filtering, Access Policy, ARP Protection, RTP/RTSP Authentication, User Authentication, HTTP/HTTPS Authentication
Face Detection	Supported
Perimeter Protection	Intrusion, Tripwire (support the classification of Human and Vehicle & Non Motor)
Smart Motion Detection	Supported
AI Search	Work together with NVR
General Parameter	
Case	Metal, Indoor & Outdoor
Protection Level	IP67
Temp. / Humidity	–30°C to +60°C (–22°F to +140°F)/Less than 95% RH
Storage Conditions	–40°C to +60°C (–40°F to +140°F)
Power Consumption	Basic: 2.5 W; Max. 5.2W
Power Supply	DC12V 2A / POE (IEEE802.3af)
Lightning Protection	Power, Network, POE all Lightning Protection, meet GB/T17626.5 and IEC61000-4-5
Dimension / Weight	122(L)*102(H)mm / 0.55KG
Approvals	
Certification	CE / FCC / RoHS
ISO	ISO9001