
4MP IR Day & Night 4G AOV Solar Camera





- 4G all Netcom Network
- ●1/3" Low Illumination Sensor, 2560*1440(4MP), Full Color Image at Night View.
- H.265 Compression,
- Full Color Dark Light Night View.
- AVO (Always Online Video) 7 Days / 24 Hours Video Recording. Don't lose any Alarm Events.
- Come with 12W Solar Power, 16000mh Batteries, can work 10-15 Days without Sunshine.
- Configure with 36W fast charge, can supply power to camera continually.
- With 1.2T support exact Humanoid Detection, support Max. 30 Meters Detection.
- Support 2 kinds of Voice Broadcast + Customization Voice Function
- Support TF card Maximum support 256G
- Multi Camera View in APP (up to 16 Cameras)

Model No.	TP-G4W	
Camera		
Image Sensor	1/3" Progressive Scan CMOS	
Max Resolution	2560*1440P	
Effective Pixels	4.0 MP	
Compression Standard	H.265 / H.264	
Framerate (fps)	Up to 15fps	
Bitrate	40Kbps∼6Mbps	
Illumination	0.1Lux	
Lens		
Lens	5MP 4.0 mm Fixed Lens / F1.0	
Max. Aperture Ratio	F No. 1.0	



Lens Mount M12 Max. Aperture F1.0 Iris Type Fixed Fixed Fixed Fixed Fixed Fixed Fixed Fixed Angle of View (V) 4.0 mm Angle of View (V) 46° Angle of View (V) B1 / B3 / B39 / B40 / B41 Interface B1 / B3 / B3 / B39 / B40 / B41 B1 / B3 / B3 / B39 / B40 / B41		1	
Fixed Fixed Focal Length & FOV Lens 4.0 mm Angle of View (H) 88° Angle of View (V) 46° Angle of View (O) 102° 4G SIM Card LTE-TDD 81 / 83 / 83 / 83 / 84 / 84 / 84 LTE-TDD 81 / 83 / 83 / 83 / 84 / 84 / 84 LTE-TDD 83 / 83 / 83 / 83 / 84 / 84 / 84 Stream Dual Stream Interface LTE-TDD 81 / 83 / 83 / 83 / 84 / 84 / 84 Audio Internal MIC Audio Internal MIC Audio Internal MIC Audio Output 1 Channel Internal MIC Audio Output 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethemet Port No For art No For art Audio Output 1 Channel Internal MIC Audio Output 2 Channel Material MIC Auto Auto	Lens Mount	M12	
Pocal Longth & FOV			
Lens 4.0 mm Angle of View (H) 88° Angle of View (O) 46° Angle of View (O) 102° Angle of View (O) 102° Angle of View (O) 102° Audic Input B1 / B3 / B3 / B3 / B3 / B4 O / B41 LTE-TDD B3 / B38 / B39 / B40 / B41 Stream Dual Stream Interface Audio Input 1 Channel Internal MIC Audio Input 1 Channel Internal Speaker Ethernet Port No Ethernet Port No Esset Support Eventum Support Exest Autionatic Gain Control Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB	• •	Fixed	
Angle of View (H) 88° Angle of View (V) 46° Angle of View (D) 102° 4G SIM Card TUE-FDD LTE-FDD B1 / B3 / B5 / B8 LTE-TDD B34 / B38 / B39 / B40 / B41 Steam Dual Stream Interface Total (Dignost) Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No TC Card Support Reset Support Exposure Mode Auto Automatic Gain Control Auto White Balance Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256CB Pan/Tilt Pan: 355° Tilt: 95° Ceneral Parameter	-		
Angle of View (V) 46° Angle of View (O) 102° 46 SIM Card LTE-FDD B1 / B3 / B5 / B8 LTE-TDD B34 / B38 / B39 / B40 / B41 Stream Dual Stream Intorface Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No FC ard Support Reset Support Function Auto White Balance Auto Motion Detection Auto Motion Detection Support Remote Control System Management, Stream Management, Alarm Management, Network Management. Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95 Coneral Parameter Webork Transmission Embedded with P6S itle P2P Transmission Protocol IR Light 8 pcs LED Array			
Angle of View (O) 102° 4G SIM Card LTE-FDD B1 / B3 / B3 / B3 / B4 / B4 / B4 LTE-TDD B34 / B38 / B39 / B40 / B41 Stream Dual Stream Interface Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No TF Card Support Reset Support Function Support Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Motion Detection System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Woway Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Processed Remote Type Transmission Protocol Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter	, , ,		
46 SIM Card LTE-FDD B1 / B3 / B3 / B3 / B4 / B4 / B4 / B4 / B4		-	
LTE-FDD B1 / B3 / B3 / B3 / B4 / B4 / B4 / B4 / B4		102°	
LTE-TDD B34 / B38 / B39 / B40 / B41 Stream Dual Stream Interface Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No TF Card Support Reset Support Exposure Mode Auto Automatic Gain Control Auto White Balance Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan-218 Pan: 355° Tilt: 95' Ceneral Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature 10°C~55°C Humidity R H 1	4G SIM Card		
Stream Dual Stream Interface Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No FC ard Support Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan-7itt Pan: 355° Tit: 95' Ceneral Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity R 10°C 50° Consumption Day<3W, Night+6W	LTE-FDD	B1 / B3 / B5 / B8	
Interface Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethemet Port No TF Card Support Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Wrow-way Talk Support Storage Up to 256GB Pan/Tit Pan: 355° Tit: 95' Ceneral Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W	LTE-TDD	B34 / B38 / B39 / B40 / B41	
Audio Input 1 Channel Internal MIC Audio Output 1 Channel Internal Speaker Ethernet Port No TF Card Support Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95' Ceneral Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C ~ 65°C Humidity RH 10% ~ 90% Power DC 5V Consumption Day<3w, Night<6W	Stream	Dual Stream	
Audio Output 1 Channel Internal Speaker Ethernet Port No TF Card Support Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W	Interface		
Ethernet Port No TF Card Support Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95' General Parameter Potwork Transmission Retwork Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W	Audio Input	1 Channel Internal MIC	
TF Card Support Reset Support Function Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W	Audio Output	1 Channel Internal Speaker	
Reset Support Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° Ceneral Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W	Ethernet Port	No	
Function Exposure Mode Auto Automatic Gain Control Auto White Balance Auto Motion Detection Support Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C ~55°C Humidity RH 10% ~90% Power DC 5V Consumption Day<3W, Night<6W	TF Card	Support	
Exposure Mode Automatic Gain Control Auto Automatic Gain Control White Balance Motion Detection Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light S pcs LED Array Lights IR Distance Working Temperature Humidity RH 10%~90% Power DC 5V Consumption Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Reset	Support	
Automatic Gain Control White Balance Auto Motion Detection Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light S pcs LED Array Lights IR Distance Working Temperature Humidity RH 10%~90% Power DC 5V Consumption Color/Material Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Function		
White BalanceAutoMotion DetectionSupportDay-Night VisionIR-CUT, Supports Color/Black SwitchRemote ControlSystem Management, Stream Management, Alarm Management, Network Management.Detection AlarmE-mail Alert, Client-end Alarm, Smartphone Message AlarmTwo-way TalkSupportStorageUp to 256GBPan/TiltPan: 355° Tilt: 95°Ceneral ParameterNetwork TransmissionEmbedded with P6S lite P2P Transmission ProtocolIR Light8 pcs LED Array LightsIR Distance30 MeterWorking Temperature-10°C~55°CHumidityRH 10%~90%PowerDC 5VConsumptionDay<3W, Night<6W	Exposure Mode	Auto	
Motion DetectionSupportDay-Night VisionIR-CUT, Supports Color/Black SwitchRemote ControlSystem Management, Stream Management, Alarm Management, Network Management.Detection AlarmE-mail Alert, Client-end Alarm, Smartphone Message AlarmTwo-way TalkSupportStorageUp to 256GBPan/TiltPan: 355° Tilt: 95°General ParameterNetwork TransmissionEmbedded with P6S lite P2P Transmission ProtocolIR Light8 pcs LED Array LightsIR Distance30 MeterWorking Temperature-10°C~55°CHumidityRH 10%~90%PowerDC 5VConsumptionDay<3W, Night<6W	Automatic Gain Control	Auto	
Day-Night Vision IR-CUT, Supports Color/Black Switch Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95' General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WXHXD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	White Balance	Auto	
Remote Control System Management, Stream Management, Alarm Management, Network Management. Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Motion Detection	Support	
Detection Alarm E-mail Alert, Client-end Alarm, Smartphone Message Alarm Two-way Talk Support Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature 4-10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Day-Night Vision	IR-CUT, Supports Color/Black Switch	
Two-way Talk Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material DC amera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Remote Control	System Management, Stream Management, Alarm Management, Network Management.	
Storage Up to 256GB Pan/Tilt Pan: 355° Tilt: 95° General Parameter Network Transmission Embedded with P6S lite P2P Transmission Protocol IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Detection Alarm	E-mail Alert, Client-end Alarm, Smartphone Message Alarm	
Pan/TiltGeneral ParameterNetwork TransmissionEmbedded with P6S lite P2P Transmission ProtocolIR Light8 pcs LED Array LightsIR Distance30 MeterWorking Temperature-10°C∼55°CHumidityRH 10%∼90%PowerDC 5VConsumptionDay<3W, Night<6W	Two-way Talk	Support	
General ParameterNetwork TransmissionEmbedded with P6S lite P2P Transmission ProtocolIR Light8 pcs LED Array LightsIR Distance30 MeterWorking Temperature-10°C~55°CHumidityRH 10%~90%PowerDC 5VConsumptionDay<3W, Night<6WColor/MaterialWhite / ABS+PCDimension (WxHxD)Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Storage	Up to 256GB	
Network TransmissionEmbedded with P6S lite P2P Transmission ProtocolIR Light8 pcs LED Array LightsIR Distance30 MeterWorking Temperature-10°C~55°CHumidityRH 10%~90%PowerDC 5VConsumptionDay<3W, Night<6W	Pan/Tilt	Pan: 355° Tilt: 95°	
IR Light 8 pcs LED Array Lights IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	General Parameter		
IR Distance 30 Meter Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Network Transmission	Embedded with P6S lite P2P Transmission Protocol	
Working Temperature -10°C~55°C Humidity RH 10%~90% Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	IR Light	8 pcs LED Array Lights	
HumidityRH 10%~90%PowerDC 5VConsumptionDay<3W, Night<6W	IR Distance	30 Meter	
Power DC 5V Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Working Temperature	-10°C∼55°C	
Consumption Day<3W, Night<6W Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Humidity	RH 10%~90%	
Color/Material White / ABS+PC Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Power	DC 5V	
Dimension (WxHxD) Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	Consumption	Day<3W, Night<6W	
	Color/Material	White / ABS+PC	
Installation Wall Mount	Dimension (WxHxD)	Camera: 114.98(W)*178.69(H)mm, Sola Panel: 330(L)*275(W)mm	
	Installation	Wall Mount	