

CAT5 VGA & Data Extender

ITEM NO.: VE01S

VE01S is designed for VGA +RS232/RS485 data signal over cost effective CAT5 cable to instead of VGA and Data cable. Used in pairs, the VGA & Data Extender is used in home or commercial applications as a smart, fast and cost-effective, eliminates costly and bulky VGA and DATA cable, allowing users can broadcast their video image or control a projector or any other RS232/RS485 device at a remote location. Ideal for sending video images to a projector and controlling it from you desk. Perfect for touch screen or auto control equipment application.

VE01S CAT5 VGA & Data Long Range Extender

Features:



- **Send VGA and RS232/RS485 Data over one CAT5 UTP cable to instead of VGA cable and data cable.**
- Dual output at transmitter: 1 VGA loop output for local, plus 1 CAT5 RJ45 output for remote side.
- Supports up to 1600x1200 @85Hz
- **Long range transmission up to 300 meters (Max.)**
- Each set including transmitter and receiver.
- Application for sending Video images to a projector and controlling it from your desk
- Built in dip switch for RS485 or RS232 option.

Installation View:





Panel View:

VE01ST




VE01SR




Installation Tips:

1. Due to the inside of CAT5 cable that the pairs of wires are twisted at different rates, AND the different quality on cable itself and installation that will cause different signal arrival time at each pair. If there are big different at arrival time, that will cause RGB skew status.. This is seen on the monitor as separation, or lack of convergence in colors. Normally it happens on long CAT 5 cable runs.



2. Recommend to use following cabling way to reduce skew status, to add special made "skew immunized adaptor", 2 pieces included at the package.



CAUTION: to avoid display equipment damaged, be sure to make correct cable connection and power for both VE01ST before connecting VE01SR

Specification:

ITEM NO.	VE01ST	VE01SR
Support Resolution	Up to 1600 x 1200 @ 85 Hz	
Transmission Distance	Up to 1000 ft. (300 m)	
Video Amplifier Bandwidth	150MHz	
Input Signals	RGB Analog (75Ω, 0.7Vp-p)	
	Sync Signal H/V Separated (TTL)	
	DB9 x 1 (RS232) / Terminal block x 1 (RS485)	
Horizontal Frequency Range	30-95KHz	
Vertical Frequency Range	50-180Hz	
VGA Connector	DB15 x 2	DB15 x 1
Link Connector	RJ45 x 1	
Power Supply	5V DC 1000mA	
Power Consumption	400mA (Max)	
CABLE FOR RJ45	CAT 5 unshielded Twisted Pair Cable (UTP) x 1	
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%	
Dimensions W x H x D mm	133 x 78.7 x 44	133 x 78.7 x 44
Weight g	390	400