

40~120M IR ILLUMINATOR



	CP-6IR	CP-9IR	CP-12IR
LED quantity	6PCS	9PCS	12PCS
IR Light Distance approach to (For Analog CAM)	Lens zoom out 40M Lens zoom in 60M	Lens zoom out 60M Lens zoom in 80M	Lens zoom out 100M Lens zoom in 120M
IR Light Distance approach to (For Digital CAM)	Lens zoom out 25M Lens zoom in 35M	Lens zoom out 35M Lens zoom in 45M	Lens zoom out 60M Lens zoom in 70M
Light Refractor	25° / 45° interlace	5° or 25° / 45° interlace	15° or 30° or 45°
IR Beam Angle	80° (One IR) 150° (Both IR)	40~80° (One IR) 150° (Both IR)	40~100° (One IR) 150° (Both IR)
Power Input	AC24(±10%) or AC90~230V (±10%)		
Rating Current	1.5A		
Power Consumption	6W	10W	12W
Temper Glass thickness	4mm		
Dimensions	170(L) X 120(W) X 115(H) mm		
Net Weight	Max 1550gm (with wall mount bracket)		
Waterproofing Criterion	IP66		
Construction	Die-Cast Aluminum Alloy		
Coating	Ivory Powder Stove		

Dimension





Side Mount

Bracket

