

# Campro

## CB-ADR-9204 (K)

### 4CH Hybrid Ultra 4K 8.0MP HD DVR



\* Support UTC (control AHD / CVI / TVI Camera via DVR by coaxial cable)



Model No.	CB-ADR-9204 (K)
Chipset / RAM	Hi3520D RAM: 4G
Operation System	Embedded Linux
Resources	Multichannel Real Time Record / Playback, Multi CH Multi User on Network Operation, USB Backup Simultaneously
System Interface	
Operation Interface	16bit True Color Graphic Menu Operation Interface
Image Display	1 / 4 Screen
Video and Audio	
Image Coding	H.264 / H.265
CVBS / HD Input	AHD / CVBS / CVI / TVI / IPC
Resolution	VGA: Max. 1080P, HDMI: Max. 4K
Video Input Mode	Any combination of analog numbers, full network 4*5MP/8*1080 /16*960P

<b>Recognize Method</b>	Automatic Identification, All AHD, All CVI, All TVI, Customized
<b>Preview</b>	4*8MN@15fps/4*5M@12fps/ 5MN@20fps/ 4*4M@15fps/ 4*3M@18fps/ 4*4MN/3MN/1080P/720P@25fps
<b>Code Capacity</b>	4*8MN@15fps/ 4*5M@12fps/5MN@20fps/4*4M@15fps/4*3M@18fps/4*4MN/3MN/1080P/720P@25fps
<b>Decode Capacity</b>	4*8MN@15fps/ 4*5M@12fps/5MN@20fps/4*4M@15fps/4*3M@18fps/4*4MN/3MN/1080P/720P@25fps
<b>Playback Definition</b>	5M/4M/3M/1080P/720P/960H/D1
<b>Audio Compression</b>	G.711A
<b>Two-Way Intercom</b>	Support
<b>Recording &amp; Playback</b>	
<b>Video Mode</b>	Manual > Alarm > Dynamic Testing > Timing
<b>Playback</b>	4CH
<b>Record Retrieval</b>	Fast play, browse play, play by time, play by event, timeline play, smart playback
<b>Intelligent Retrieval</b>	Display whether the specified area has motion in different colors
<b>Backup &amp; Storage</b>	
<b>Space Occupation</b>	3M/4M/5M ~ 15G/day* channel; 4MN/3MN/1080P 10~15G/day* channel; 720P ~10G/day* channel; 960H 6~10G/day* channel; Audio: 691.2M/day* channel
<b>Recording Storage</b>	Local Hard Disk / Network
<b>Backup Mode</b>	Network backup, USB mobile hard disk, USB burning, SATA burning
<b>VMS</b>	
<b>VMS / Mobile App</b>	IE / Web / CAMPRO VMS / P6S Lite App
<b>P2P</b>	Support IOS / Android / PC
<b>Mobile APP Function</b>	Multi-screen monitoring, audio monitoring, mobile video recording, capture, PTZ control, remote video playback, device list saving
<b>Other Function</b>	
<b>AI Function</b>	Face Detection, Face List Playback, AI Overline Alarm, AI Area Intrusion Alarm, AI Area Enter Alarm, AI Area Exit Alarm, PIR Detection, Human Shape Detection (IP Cam)
<b>Motion Detection</b>	192(16x12) Testing Areas can be set for each Image, can set Multiple Sensitivity
<b>UTC</b>	Support
<b>PTZ</b>	Support
<b>Camera Soft. Updated</b>	Support
<b>Dynamic 3D DNR</b>	Support
<b>Port</b>	
<b>Video Input</b>	4CH BNC
<b>Video Output</b>	1CH VGA, 1CH HDMI
<b>Loop Output</b>	N/A, (Optional 1CH Loop Output)
<b>Audio Input</b>	4CH RCA
<b>Audio Output</b>	1CH RCA
<b>Alarm Input</b>	N/A, (Optional 4CH Alarm Input)

Alarm Output	N/A, (Optional 1CH Alarm Output)
Network Port	RJ45 10M / 100M Self-Adapt to Ethernet Interface
RS485	1 x RS485
USB Port	2 x USB2.0
HDD Port	Support 2 x 8TB HDD (Seagate)
WIFI Port	4G WIFI Extend via USB (Coming Soon)
Remote Controller	Optional
Structure	
Dimensions	330mm*255mm*53mm / 1.3KG (Not Including HDD)
Operation Temp.	-5°C - 55°C
Humidity	10 - 90%
Power Consumption	< 15W (HDD not included)
Power Supply	DC12V / 5A
Certification	CE / FCC / RoHS