

CVBS / HD Input

Video Input Mode

Resolution

16CH Hybrid Ultra 4K 8.0MP HD DVR CAMPRO HDD POWER IN \bigcirc \odot 0 * Support UTC (control AHD / CVI / TVI Camera via DVR by coaxial cable) Model No. CB-ADR-9216 (K) Hi3531D RAM: 16G Chipset / RAM **Operation System** Embedded Linux Multichannel Real Time Record / Playback, Multi CH Multi User on Network Operation, USB Backup Resources Simultaneously **System Interface** 16bit True Color Graphic Menu Operation Interface **Operation Interface** 1 / 4 / 6 / 8 / 9 / 16 Screen **Image Display** Video and Audio **Image Coding** H.264 / H.265

AHD / CVBS / CVI / TVI / IPC VGA: Max. 1080P, HDMI: Max. 4K

Any combination of analog numbers, full network 4*5MP/8*3MP/16*1080P

Campro

Recognize Method	Automatic Identification, All AHD, All CVI, All TVI, Customized
Preview	16*8MN@15fps/ 16*5M@12fps/5MN@20fps/ 16*4M@15fps/ 16*3M@18fps/ 16*4MN/3MN/1080P/720P@25fps
Code Capacity	16*8MN@8fps/ 16*5M@6fps/ 5MN@12fps/16*4M@8fps/ 16*3M@10fps/16*3MN@18fps/ 16*4MN/1080P@15fps/ 16*720P@25fps
Decode Capacity	16*8MN@8fps/ 16*5M@6fps/ 5MN@12fps/16*4M@8fps/ 16*3M@10fps/16*3MN@18fps/ 16*4MN/1080P@15fps/ 16*720P@25fps
Playback Definition	8MN/5M/4M/3M/1080P/720P/960H/D1
Audio Compression	G.711A
Two-Way Intercom	Support
Recording & Playback	
Video Mode	Manual > Alarm > Dynamic Testing > Timing
Playback	16CH
Record Retrieval	Fast play, browse play, play by time, play by event, timeline play, smart playback
Intelligent Retrieval	Display whether the specified area has motion in different colors
Backup & Storage	
Space Occupation	3M/4M/5M ~15G/day* channel; 4MN/3MN/1080P 10~15G/day* channel; 720P ~10G/day* channel; 960H 6~10G/day* channel; Audio: 691.2M/day* channel
Recording Storage	Local Hard Disk / Network
Backup Mode	Network backup, USB mobile hard disk, USB burning, SATA burning
VMS	
VMS / Mobile App	IE / Web / CAMPRO VMS / P6S Lite App
P2P	Support IOS / Android / PC
Mobile APP Function	Multi-screen monitoring, audio monitoring, mobile video recording, capture, PTZ control, remote video playback, device list saving
Other Function	
AI Function	Face Detection, Face List Playback, AI Overline Alarm, AI Area Intrusion Alarm, AI Area Enter Alarm, AI Area Exit Alarm, PIR Detection, Human Shape Detection (IP Cam)
Motion Detection	192(16x12) Testing Areas can be set for each Image, can set Multiple Sensitivity
UTC	Support
PTZ	Support
Camera Soft. Updated	Support
Dynamic 3D DNR	Support
Port	
Video Input	16CH BNC
Video Output	1CH VGA, 1CH HDMI
Loop Output	1CH CVBS
Audio Input	2CH RCA
Audio Output	1CH RCA
Alarm Input	N/A, (Optional 4CH Alarm Input)

Campro Alarm Output N/A, (Optional 1CH Alarm Output) **Network Port** RJ45 10M / 100M Self-Adapt to Ethernet Interface **RS485** 1 x RS485 **USB** Port 2 x USB2.0 HDD Port Support 2 x 8TB HDD (Seagate) WIFI Port 4G WIFI Extend via USB (Coming Soon) **Remote Controller** Optional Structure **Dimensions / Weight** 330mm*255mm*53mm / 1.3KG (Not Including HDD) Operation Temp. -5°C - 55°C

10 - 90%

< 15W (HDD not included)

DC12V / 5A

CE / FCC / RoHS

Humidity

Power Supply

Certification

Power Consumption