

Campro

CB-ADR-9204 (E)

4CH Hybrid 5.0MP Lite HD DVR



* Support UTC (control AHD / CVI / TVI Camera via DVR by coaxial cable)



Model No.	CB-ADR-9204 (E)
Chipset / RAM	Hi3520D RAM: 2G
Operation System	Embedded Linux
Resources	Multichannel Real Time Record / Playback, Multi CH Multi User on Network Operation, USB Backup Simultaneously
System Interface	
Operation Interface	16bit True Color Graphic Menu Operation Interface
Image Display	1 / 4 Screen
Video and Audio	
Image Coding	H.264 / H.265
CVBS / HD Input	AHD / CVBS / CVI / TVI / IPC
Resolution	VGA: Max. 1080P, HDMI: Max. 1080P
Video Input Mode	Analog digital Any combination, full network 4*5MP/8*1080P

Recognize Method	Automatic Identification, All AHD, All CVI, All TVI, Customized
Preview	4*5MN@20fps/4*4MN@25fps/4*3MN@25fps/4*1080P@25fps/4*720P@25fps 5 IN 1
Code Capacity	4*5MN@12fps/4*4MN@18fps/4*3MN@18fps/4*1080P@18fps/4*720P@25fps 5 IN 1
Decode Capacity	1*5MN@12fps/4*4MN@18fps/4*3MN@18fps/4*1080P@18fps/4*720P@25fps 5 IN 1
Playback Definition	4MN/3MN/1080N/720P/960H/D1
Audio Compression	G.711A
Two-Way Intercom	Support
Recording & Playback	
Video Mode	Manual > Alarm > Dynamic Testing > Timing
Playback	4CH
Record Retrieval	Fast playback, browse playback, play by time, play by event, timeline playback, smart Playback
Intelligent Retrieval	Displays whether there is movement in the specified area in a different color
Backup & Storage	
Space Occupation	4MN/3MN/1080P 10~15G/day* channel; 720P ~10G/day* channel; 960H 6~10G/day* channel; Audio: 691.2M/day* channel
Recording Storage	Local Hard Disk / Network
Backup Mode	Network backup, USB removable hard disk, USB burning, SATA burning
VMS	
VMS / Mobile App	IE / Web / CAMPRO VMS / P6S Lite App
P2P	Support IOS / Android / PC
Mobile APP Function	Multi-screen monitoring, audio listening, mobile phone video, capture, cloud console control, remote video playback, device list preservation
Other Function	
AI Function	Face Detection, Face List Playback, PIR Detection, Human Shape Detection (IP Cam)
Motion Detection	192(16x12) Testing Areas can be set for each Image, can set Multiple Sensitivity
UTC	Support
PTZ	Support
Camera Soft. Updated	Support
Dynamic 3D DNR	Support
Port	
Video Input	4CH BNC
Video Output	1CH VGA, 1CH HDMI
Loop Output	1CH CVBS
Audio Input	4CH RCA
Audio Output	1CH RCA
Alarm Input	N/A, (Optional 4CH Alarm Input)
Alarm Output	N/A, (Optional 1CH Alarm Output)
Network Port	RJ45 10M / 100M Self-Adapt to Ethernet Interface
RS485	1 x RS485
USB Port	2 x USB2.0

HDD Port	Support 2 x 8TB HDD (Seagate)
WIFI Port	4G, WIFI (extended via USB)
Remote Controller	Optional
Structure	
Dimensions / Weight	330mm*255mm*53mm / 1.0KG (Not Including HDD)
Operation Temp.	-5°C - 55°C
Humidity	10 - 90%
Power Consumption	< 15W (HDD not included)
Power Supply	DC12V / 5A
Certification	CE / FCC / RoHS